



## SERIES 2000

Motor Driven and Hand Crank

# Aluminum Spray Reel



E23018 H

Aluminum construction is **50% lighter in weight** than carbon steel and corrosion resistant

3/4" fluid path constructed of 316 stainless steel is **designed to handle harsh chemicals**

Available with either a stainless steel or carbon steel swivel

**Aluminum alloy drum** withstands crush and warping under high pressure and heat

Hardware includes a two-coat plating process that **resists salt spray and acids**

Includes spring loaded latching mechanism and drag brake to control over spooling



### FINISH

Available in tumbled natural or polyester powder-coated for salt spray resistance and up to 20% bleach exposure.



### VERSATILE DESIGN

Innovative design allows for the handle, motor, or swivel to be easily swapped from one side to the other.



Interactive  
Reel Catalog



reelcraft.com

Model without Hose & Bumper	Finish	Shipping Weight		Max Pressure	
		lbs	kg	psi	bar
<b>Hand Crank Medium Pressure Reels</b>		Maximum Temperature 150°F (65°C) Maximum Working Pressure is at 70°F (20°C)			
C23012	Powder Coated	21.5	10	3000	207
C23018	Powder Coated	23.5	10	3000	207
C23022	Powder Coated	25	11	3000	207
C23012 310	Tumbled Natural	21.5	10	3000	207
C23018 310	Tumbled Natural	23.5	10	3000	207
C23022 310	Tumbled Natural	25	11	3000	207
<b>12 V DC Motor Driven Medium Pressure Reels</b>		Maximum Temperature 150°F (65°C) Maximum Working Pressure is at 70°F (20°C)			
E23012	Powder Coated	24.5	11	3000	207
E23018	Powder Coated	26.5	12	3000	207
E23022	Powder Coated	28	13	3000	207
E23012 310	Tumbled Natural	24.5	11	3000	207
E23018 310	Tumbled Natural	26.5	12	3000	207
E23022 310	Tumbled Natural	28	13	3000	207
<b>Hand Crank High Pressure Reels</b>		Maximum Temperature 210°F (99°C) Maximum Working Pressure is at 70°F (20°C)			
C23012 H	Powder Coated	21.5	10	4500	310
C23018 H	Powder Coated	23.5	10	4500	310
C23022 H	Powder Coated	25	11	4500	310
C23012 H 310	Tumbled Natural	21.5	10	4500	310
C23018 H 310	Tumbled Natural	23.5	10	4500	310
C23022 H 310	Tumbled Natural	25	11	4500	310
<b>12 V DC Motor Driven High Pressure Reels</b>		Maximum Temperature 210°F (99°C) Maximum Working Pressure is at 70°F (20°C)			
E23012 H	Powder Coated	24.5	11	4500	310
E23018 H	Powder Coated	26.5	12	4500	310
E23022 H	Powder Coated	28	13	4500	310
E23012 H 310	Tumbled Natural	24.5	11	4500	310
E23018 H 310	Tumbled Natural	26.5	12	4500	310
E23022 H 310	Tumbled Natural	28	13	4500	310

Medium pressure reels supplied with Stainless Steel 3000 psi swivel.  
High pressure reels supplied with Carbon Steel 4500 psi swivel.



### OPTIONAL SPRAY REEL ACCESSORIES



#### Side Wind Roller Guide Kit

Our SW Roller Guide Kit makes it easier to pull the hose at higher elevations.

#### Bottom Wind Roller Guide Kit

Our BW Roller Guide Kit makes it easier to pull the hose at lower elevations.

#### Stacking Brackets Kit

Stacking brackets are easy to install, allowing you to customize your setup to suit your needs.

#### Whip Hose—Chemical

- 3/4" ID, Stainless Steel Ends  
- 200 PSI

#### Whip Hose—Power Wash

- 1/2" ID  
- Plated Carbon Steel Ends  
- 4300 PSI

Hose Diameter				
ID	3/8"	1/2"	5/8"	3/4"
OD	0.71"	0.85"	0.94"	1.08"
Spool Width	Hose Capacity			
12"	300'	200'	150'	125'
18"	500'	300'	250'	200'
22"	600'	350'	300'	250'

### Dimensions - Width

	Spool	12"	18"	22"
<b>A</b>	Motor Driven	28"	34"	38"
<b>A</b>	Hand Crank	25"	31"	35"
<b>B</b>	Mounting Pattern	16.88"	22.88"	26.88"
<b>C</b>	Mounting Pattern	11"	17"	21"
<b>D</b>	Mounting Pattern	18"	24"	28"

